

Declaration of Performance

(model in accordance with delegated regulation Nr. 574/2014 of the European Commission)
 Nr BRD017

1.	Unique identification code of product-type	Premiumfol EPDM thickness 0.50, 0.75 and 1.00 mm, Nr BRD017	
2.	Intended use/uses	Elastic EPDM strips for the application of vapour barrier layers in buildings	
3.	Manufacturer	Berdal Rubber & Plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherlands	
4.	Authorised representative	Not applicable	
5.	The system or systems for assessing and verifying performance resistance (AVCP)	AVCP 3	
6a.	Harmonised standard	EN 13984:2013	
	Notified authority	Applus/LGHI Technological center A.S. notification number 0370	
7.	Declared performance (s)	Essential features:	Performances:
		Fire reaction	Classe E
		Waterimpermeability:	'Pass' at 2 kPa
		Resistance to shock load:	> 300 mm
		Water vapour transmission rate (Sd)	$\mu=33200$
		Adhesion strengths	>200 N/50 mm
		Maximum elongation strength:	>6.5 Mpa
		Ductility at maximum strength	>300%
		Tear resistance	>25 N
		Duribility regarding to: Water vapor transmission rate at artificial ageing	Pass
Chemicals	Pass		

The performance of the product identified is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with (UE) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer.

B.M.D. van Kamperdijk, General Manager

Almelo, The Netherlands, 1 March 2018