

Declaration of Performance

(model in accordance with delegated regulation Nr. 574/2014 of the European Commission)

DoP nr. BRD018

1.	Unique identification code of product-type	Premiumfol EPDM thickness 1.00, 1.20, 1.50, 2.00 mm, Nr BRD018	
2.	Intended use/uses	EPPDM for roof water sealing. Application as single layer roofing	
3.	Manufacturer	Berdal Rubber & Plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherlands	
4.	Authorised representative	Not applicable	
5.	The system or systems for assessing and verifying performance resistance (AVCP)	AVCP 2+	
6a.	Harmonised standard	EN 13956:2013	
	Notified authority	AENOR, notification nr.: 0099. Ref: Certificate of Conformance A85/0044	
7.	Declared performance (s)	Essential features:	Performances:
		Fire reaction	Classe E
		External fire reaction	Broof (t1)
		Waterimpermeability:	'Pass' at 60 kPa
		Tensile Strength	≥ 9.0 Mpa
		Resistance to shock load	≥ 200 mm
		Elongation at break	≥ 300 %
		Static performance resistance:	> 25 kg.
		Tear resistance	> 20 N
		Adhesion strengths - Tensile/shear resistance - Peel resistance	≥ 200 N/50 mm ≥ 25 N/50 mm
Duribility regarding to: - waterimpermeability - UV resistance - artificial ageing (2 kPa)	Pass Pass Pass		

The performance of the product identified is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with (UE) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer.

B.M.D. van Kamperdijk, General Manager

Almelo, The Netherlands, 1 March 2018